
Network
102
100
Computer-Based
Instruments
142
Computer
GPIB
122
Network
112
Software
104
PXI
118
VXI/VME
116
Plug-In-Data
Acquisition Boards
114
134
124
132
Image
Acquisition
Signal
Conditioning
126
138
Unit Under Test
150
Motion Control
136

FIG. 1A


Network
102
MMI/SCADA
Computer
160
Network
Data Acquisition
Software
104
FieldPoint
Plug-In-Data
Acquisition
Boards
114
124
184
Serial
Signal
Conditioning
126
182
PLC
176
Fieldbus
172
PXI
118
170
134
132
Image
Acquisition
138
Motion
Control
136
Stimulus
Control
150
Temperature
Pressure
Flow
Process

FIG. 1B


12
Main Memory
166
CPU
160
Memory
Controller
164
Host Bus 162
Bus Controller
168
Expansion Bus 170
Video
180
Hard Drive
182
GPIB Card
122
Data
Acquisition
Card
114
Reconfigurable
Instrument
120
GPIB Bus 112

Figure 2



Figure 3



Figure 4


Install Measurement Hardware Device(s)
502
Configure Measurement Hardware Device(s)
504
Configure Measurement Task with Measurement Task Specifier to Generate Measurement Task Specification
506
Experts Analyze Measurement Task Specification, Validate Measurement Task Specification, and Generate Run Time Specification
508
Create a Runtime to Perform Measurement Task
510

Figure 5



High-Level Architecture

Figure 6


System Configuration and Task Specification
System Configuration Tools
700
DAQ MAX Provider
plugs in
MAX
704
702
produces system configuration
System Storage Tools
710
Measurements System Configuration
706
extends
MIO System Configuration
708
stored in
712
MXS
retrieves system configuration
Interactive and Application Programming Interfaces
730
Measurements Configuration Tool
714
extends
MIO Configuration Tool Plug-in
716
Measurements API for LabVIEW
718
extends
MIO Extensions to Measurements API for LabVIEW
722
Measurements API for Measurement Studio Tools for Visual C++
724
extends
MIO Extensions to Measurements API for Measurement Studio Tools for Visual C++
726
Measurements API for C
728
extends
MIO Extensions to Measurements API for C
732
Measurements API for Measurement Studio Tools for Visual Basic
734
extends
MIO Extensions to Measurements API for Measurement Studio Tools for Visual Basic
736
produces measurements task specification
Task Specification
740
Measurements MSOs
742
extends
MIO MSOs
744
stored in
712
MXS

Figure 7A


Compiling Task Specification to Task Run-time Specification
Task Specification
740
Measurements MSOs
extends
742
744
MIO MSOs
stored in
712
MXS
compiles
752
Expert System
750
Measurements Run-time Experts
Measurements Streaming Experts
756
754
MIO Experts
Routing Experts
758
registers with
759
Measurements Expert Library
produces
Task Run-time Specification
770
Measurements Run-time Primitive Settings
772
Measurements Streaming Primitive Settings
774
Routing Primitive Settings
776
MIO Primitive Settings
778
stored in
712
MXS
retrieves for making decisions
refers to for matching experts to the task specification
System Configuration Storage
710
Measurements System Configuration
706
extends
708
MIO System Configuration
stored in
712
MXS
Expert Registration Storage
760
762
MIO Expert Registrations
Routing Expert Registrations
766
764
Measurements Run-time Expert Registrations
Measurements Streaming Expert Registrations
768
stored in
712
MXS

Figure 7B


Building Task Run-time from Task Run-time Specification
Task Run-time Specification
770
Measurements Run-time Primitive Settings
772
Measurements Streaming Primitive Settings
774
Routing Primitive Settings
776
MIO Primitive Settings
778
stored in
712
MXS
retrieves
Run-time Builder
780
Measurements Run-time Builder
782
creates primitive supervisors for each primitive settings
784
Measurements Run-time Primitive Supervisors
Measurements Streaming Primitive Supervisors
788
786
MIO Primitive Supervisors
Routing Primitive Supervisors
789
builds
Task Run-time
790
Measurements Run-time
792
managed by
794
Routing Primitives and Supervisors
Measurements Streaming Primitives and Supervisors
798
796
MIO Primitives and Supervisors
Measurements Run-time Primitives and Supervisors
799

Figure 7C


Executing Tasks
Task Run-time
790
Measurements Run-time
792
managed by
Routing Primitives and Supervisors
794
Measurements Streaming Primitives and Supervisors
798
MIO Primitives and Supervisors
796
Measurements Runtime Primitives and Supervisors
799
commits
reserves and unreserves
reads and writes
starts and stops
sets and gets
Interactive and Application Programming Interfaces
730
Measurements API for Measurement Studio Tools for Visual C++
714
Measurements API for LabVIEW
718
extends
716
MIO Extensions to Measurements API for Measurement Studio Tools for Visual C++
722
MIO Extensions to Measurements API for LabVIEW
Measurements API for Measurement Studio Tools for Visual Basic
724
Measurements API for C
728
726
MIO Extensions to Measurements API for Measurement Studio Tools for Visual Basic
732
MIO Extensions to Measurements API for C
Measurements API for Measurement Studio Tools for Visual Basic
734
736
MIO Extensions to Measurements API for Measurement Studio Tools for Visual Basic

Figure 7D


Packages for System Configuration and Task Specification
System Configuration Tools
810
U
DAQ MAX Provider
812
814
U
MAX
Data Dictionaries
800
U
Measurements MSO Data Dictionary
802
Measurements U System Configuration Data Dictionary
806
U
MIO MSO Data Dictionary
U
MIO System Configuration Data Dictionary
804
808
U
MXS
809
API Libraries
820
U
Measurements API for LabVIEW Library
822
Measurements API U for Measurement Studio Tools for Visual C++ Library
824
823
825
U
MIO Extensions to Measurements API for LabVIEW Library
MIO Extensions to U Measurements API for Measurement Studio Tools for Visual C++ Library
U
Measurements API for C Library
826
Measurements API U for Measurement Studio Tools for Visual Basic Library
828
827
829
U
MIO Extensions to Measurements API for C Library
MIO Extensions U to Measurements API for Measurement Studio Tools for Visual Basic Library
U user-mode component
K kernel-mode component
UK dual-mode component

Figure 8A


Packages for Compiling Task Specification to Run-time Specification
Measurements System Data Dictionaries
830
Measurements MSO Data Dictionary
U
802
MIO MSO Data Dictionary
U
804
Measurements System Configuration Data Dictionary
U
806
MIO System Configuration Data Dictionary
U
808
Measurements Run-time Primitive Settings Data Dictionary
U
834
Measurements Streaming Primitive Settings Data Dictionary
U
835
Routine Primitive Settings Data Dictionary
U
836
MIO Primitive Settings Data Dictionary
U
837
Expert Registration Data Dictionary
U
832
MXS
U
809
Expert System
840
Measurements Expert Library
U
842
Routing Expert Library
U
844
Measurements Streaming Expert Library
U
848
MIO Expert Library
U
846
Measurements Run-time Expert Library
U
849
User-Mode Run-time System
850
Measurements Run-time Library
U
852
Measurements Streaming Run-time Library
U
856
Routing Run-time Library (all primitive settings and user-mode primitive supervisors)
U
854
MIO Run-time Library (all primitive settings and user-mode primitive supervisors)
U
858
U user-mode component
K kernel-mode component
UK dual-mode component

Figure 8B


Packages for Building Task Run-time from Run-time Specification
Primitive Settings Data Dictionaries
860
836
Routing Primitive Settings Data Dictionary
U
834
Measurements Run-time Primitive Settings Data Dictionary
U
837
MIO Primitive Settings Data Dictionary
U
835
Measurements Streaming Primitive Settings Data Dictionary
U
809
MXS
U
User- and Kernel-Mode Run-time System
880
882
Routing Driver (driver and primitives)
UK
884
MIO Driver (driver and primitives)
UK
Measurements Run-time Library
UK
852
856
Measurements Streaming Run-time Library
UK
886
Measurements Streaming Library
UK
854
Routing Run-time Library (primitive settings and primitive supervisors)
UK
858
MIO Run-time Library (primitive settings and primitive supervisors)
UK
U user-mode component
K kernel-mode component
UK dual-mode component

Figure 8C


Packages for Executing Task Run-time
User- and Kernel-Mode Run-time System
880
882
Routing Driver (driver and primitives)
UK
884
MIO Driver (driver and primitives)
UK
856
Measurements Streaming Run-time Library
UK
886
Measurements Streaming Library
UK
Measurements Run-time Library
UK
852
854
Routing Run-time Library (primitive settings and primitive supervisors)
UK
858
MIO Run-time Library (primitive settings and primitive supervisors)
UK
API Libraries
820
U
Measurements API for LabVIEW Library
822
Measurements API for Measurement Studio Tools for Visual C++ Library
U
824
823
U
MIO Extensions to Measurements API for LabVIEW Library
825
MIO Extensions to Measurements API for Measurement Studio Tools for Visual C++ Library
U
826
U
Measurements API for for C Library
828
Measurements API for Measurement Studio Tools for Visual Basic Library
U
827
U
MIO Extensions to Measurements API for C Library
829
MIO Extensions to Measurements API for Measurement Studio Tools for Visual Basic Library
U
U user-mode component
K kernel-mode component
UK dual-mode component

Figure 8D


State Diagram for Measurement Tasks
The Constructed state corresponds to the state of the task at the end of the "Building Task Run-Time from Task Run-Time Specification" static diagram.
set
get
set/get
create task
verify, get
construct
Unverified
902
Verified
904
Constructed
906
destroy task
set
destroy
The Unverified state corresponds to the state of the task during the "Task Specification" static diagram
The Verified state corresponds to the state of the task at the end of the "Compiling Task specification to Task Run-Time Specification" static diagram.
unreserve
reserve
set/get
set/get
set/get
A small subset of properties may be accessed in the Running state. This occurs by modifying the primitives directly while the hardware is running.
start
commit
Running
912
Committed
910
Reserved
908
stop
uncommit
The Reserved, Committed, and Running states correspond to the state of the task during the "Executing Task" static diagram.
State transitions may occur implicitly. For example, if the start action is invoked when the task is in the Constructed state, the task will transition through the Reserved and Committed states implicitly when transitioning to the Running state. The implicit state transitions are also symmetric. In this example, if the stop action is invoked, the task will transition through the Committed and Reserved states implicitly when transitioning back to the Constructed state.

Figure 9


GUI Framework
1002
Block .INI File
1004
Timing VI,
Advanced VIs,
Synchronization
VI, etc.
1005
Block Icon
1006
Main Template VI
1008
Main State VI
1010
Measurement
Class VI
1012

Figure 10


Measurement Task Configurator
Undo
Redo
Apply
Add
Voltage Measurement
Channel Setup
Channel List
Voltage 0
Voltage 1
Voltage 2
Voltage 3
Channels
Settings
Details
Input Range
Max
10.0000
V
Min
-10.0000
V
Apply settings to all Channels
Sensor Type
<No Sensor>
Timing Setup
Mode
Acquire 1 Sample
Acquire N Samples
Acquire Continuously
Timing
100
Samples
1000.00
Rate (Hz)
Block Setup
Advanced
Welcome to the
Task Configurator
Voltage
Welcome to the voltage measurement setup.
Steps:
1. Click Add New Measurements.
2. Select the desired terminals.
Note: Hold <Shift> to select multiple terminals.
3. Press <Enter> or click the check button.
4. Choose the desired settings for your measurements.
5. Save and exit or generate code.

Figure 11


Blocks
Blocks
Acceleration
AnalogFreq
Current
PulseTrain
Resistance
Strain
Temperature
Voltage

Figure 12A


Measurement Task Configurator
Undo
Redo
Apply
Add...
Voltage
Voltage Measurement
Channel Setup
Channel List
Voltage 0
Voltage 1
Voltage 2
Voltage 3
Channels
Settings
Details
Input Range
Max
10.0000
V
Min
-10.0000
V
Apply settings to all Channels
Sensor Type
<No Sensor>
Timing Setup
Mode
Acquire 1 Sample
Acquire N Samples
Acquire Continuously
Timing
100
Samples
1000.00
Rate (Hz)
Block Setup
Advanced
Welcome to the
Task Configurator
Voltage
Welcome to the voltage measurement setup.
Steps:
1. Click Add New Measurements.
2. Select the desired terminals.
Note: Hold <Shift> to select multiple terminals.
3. Press <Enter> or click the check button.
4. Choose the desired settings for your measurements.
5. Save and exit or generate code.

Figure 12B


Measurement Task Configurator
Undo
Redo
Apply
Add...
Voltage Measurement
Channel Setup
Channel List
Voltage 0
Voltage 1
Voltage 2
Voltage 3
Channels
Settings
Details
Add Channels
Selection List
PCI-MIO-16E-1 (Dev1)
Ch 0
Ch 1
Ch 2
Ch 3
Ch 4
Ch 5
Ch 6
Mode
Create New
Add Existing
Copy Existing
Select desired terminals from above to add to the channel list for your task. To select multiple items, hold down the <Shift> key. Click the arrow or press <Enter> when complete.
Timing Setup
Mode
Acquire 1 Sample
Acquire N Samples
Acquire Continuously
Timing
100 Samples
1000.00 Rate (Hz)
Block Setup
Advanced
Welcome to the
Task Configurator
Voltage
Welcome to the voltage measurement setup.
Steps:
1. Click Add New Measurements.
2. Select the desired terminals.
Note: Hold <Shift> to select multiple terminals.
3. Press <Enter> or click the check button.
4. Choose the desired settings for your measurements.
5. Save and exit or generate code.

Figure 12C


Measurement Task Configurator
Undo
Redo
Apply
Add...
Voltage Measurement
Channel Setup
Channel List
Voltage 0
Voltage 1
Voltage 2
Voltage 3
Channels
Settings
Details
Custom Scaling
<No Scale>
Channel Name
Voltage 0
HW Terminal
Modify
PCI-MIO-16E-1 (Dev1)::Ch 0
Measurement & Automation Explorer
Channel is local to Task
Change channel type
Timing Setup
Mode
Acquire 1 Sample
Acquire N Samples
Acquire Continuously
Timing
100 Samples
1000.00 Rate (Hz)
Block Setup
Advanced
Welcome to the
Task Configurator
Voltage
Welcome to the voltage measurement setup.
Steps:
1. Click Add New Measurements.
2. Select the desired terminals.
Note: Hold <Shift> to select multiple terminals.
3. Press <Enter> or click the check button.
4. Choose the desired settings for your measurements.
5. Save and exit or generate code.

Figure 12D


Measurement Task Configurator
Undo
Redo
Apply
Add
Task Data
Scaled
Data Format
Waveform
Data Type
Stream to Disk
File Path
C:\MyData\data.bin
Post to the Internet
URL
http://localhost.MyData
Advanced Task Configuration
Reset all to Default
Triggering
Start
Source
Slope
Level
PFI 0
Rising
0.0000
Trigger Type
Analog Level
Stop
Source
Edge
PFI 0
Rising
Trigger Type
Digital Edge
Pre-Trigger Samples
0
Pause
Trigger Type
<None>
Block Setup
Advanced
Welcome to the
Task Configurator
Voltage
Welcome to the voltage measurement setup.
Steps:
1. Click Add New Measurements.
2. Select the desired terminals.
Note: Hold <Shift> to select multiple terminals.
3. Press <Enter> or click the check button.
4. Choose the desired settings for your measurements.
5. Save and exit or generate code.

Figure 13



Figure 14


Channel "myVoltage1"
Terminal 5
1512
Channel "myVoltage2"
Terminal 6
1514
SCXI 1001
Slot 0
Device 0
1502
SCXI 1100
Slot 1
Device 1
1504
ab0/trig0
1516A
SCXI 1001
Slot 0
Device 2
1506
SCXI 1102
Slot 1
Device 3
1508
ab0/trig0
1516B
mch0
1518A
scanclk
1520A
mch0
1518B
scanclk
1520B
ai1
1524
ai0
1522
scanclk
1520C
MIO PCI-
6032E
Device 4
1510
Fully-Qualified Channel Paths:
myVoltage1: /dev4:ai0/dev0/dev1:5
myVoltage2: /dev4:ai1/dev2/dev3:6

Figure 15



Voltage On Two Channels with Two SCXI Modules in Two SCXI Chassis Connected to an MIO DAQ Device

Figure 16



Create Device Expert Call Tree



Figure 17



Create Channel Experts



Figure 18



Deserialize Named Channel MSOs



Figure 19



Configure Timing Experts



Figure 20



MSO Set Calls



Figure 21



Analyze Channels



Figure 22



Analyze Timing



Figure 23



Compile



Figure 24A



Commit



Figure 24B



Start



Figure 24C



Read



Figure 24D



Stop



Figure 24E



Uncommit



Figure 24F



Expert Call Tree

Figure 25 Use Case: Multi-Chassis SCXI Finite Acquisition Using An MIO


Expert System Analyzes Measurement Task Specificaion
2602
Select At Least One Expert To Populate Candidate Run Time Specifications
2604
Each Expert Analyzes Measurement Task (or Sub-Task) Specification
2606
Each Expert Populates a Candidate Run Time Specification
2608
Candidate Run Time Specification Complete?
2610
No
Submit Unsolved Portion of Measurement Task Specification to Expert System as New Measurement Sub-Task Specification
2612
Yes
Expert System Calculates Metrics for Each Candidate Run Time Specification
2614
Expert System Selects One Candidate Run Time Specification Based On Calculated Metrics
2616

Figure 26


MIO AI Task
Specification
2704
MIO AI Data
Transfer Expert
2702
DMA
Implementation
2706
Interrupt
Implementation
2708

Figure 27



Figure 28


Specification 1
2902
Expert 1
2904
Specification 2
2906
Expert 2
2908

Figure 29


Task
Specification
3002
Runtime
Configuration
3000
Runtime
Specification
3006
System
Configuration
3004

Figure 30


3102A
3106A
3104
3106B
3102B
3108
timebase_out
rtsi0
rtsi1
rtsi7
Device 1
Device 2
timebase_in
3110
3104A-H

Figure 31


Specification 0
3202
Device 1
MUX Expert
3204A
Specification 1
3206
Connector
Expert
3208A
Specification 2
3210
Connector
Expert
3208B
Specification 3
3212
Device 2
MUX Expert
3204B
Specification 4
3214
Completion
Expert
3216
Done

Figure 32


3302A
Device 1
3106C
3106D
Device 2
3302B
3104
3304A
3304B
digitizer
digitizer
rtsi0
rtsi1
rtsi7
ai0
ai0
3104A-H
3306A
3306B

Figure 33


Specification 0
3402
Group
Splitting
Expert
3404
Specification 1
3406
Device 1
Acquisition
Expert
3408A
Specification 2
3410
Device 2
Acquisition
Expert
3408B
Specification 3
3412
Routing
Experts
3414
Specification 4
3414
Completion
Expert
3416
Done

Figure 34


3502
3504
3508B
Device 1
DMM
3506
Device 3
Switch
vmc
trig_in
trig_in
trig_out
0
3516
1
3508A
3512
ai0
com
31
3510
3514

Figure 35


Specification 0
3602
Switch
Scanning
Expert
3604
Specification 1
3606
Routing
Experts
3608A
Specification 2
3610
DMM
Acquisition
Expert
3612
Specification 3
3614
Routing
Experts
3608B
Specification 4
3616
Completion
Expert
3618
Done

Figure 36


Task
Specification
3702
Out-of-the-Box
Configuration
3700
Runtime
Specification
3706
Required
Hardware
Connections
3708
System
Configuration
3704

Figure 37


Task Specification 3802
Point-of-Sale Configuration 3800
Runtime Specification 3806
Required Hardware and Hardware Connections 3808
System Configuration 3804

Figure 38



Simultaneous Buffered Analog Input And Single Point Digital Output With Single-Threaded Driver (Prior Art)

Figure 39A (Prior Art)



Simultaneous Buffered Analog Input And Single Point Digital Output With Multi-Threaded Driver

Figure 39B



Simultaneous Triggered Buffered AI/AO (Prior Art)

Figure 40A



Simultaneous Triggered Buffered AI/AO

Figure 40B



Sharing Scan Clock Across Two E-Series Devices (Prior Art)

Figure 41A



Sharing Scan Clock Across Two E-Series Devices

Figure 41B



Sharing Clock And Trigger, Buffered AI & DI

Figure 42



Acquire N Scans External Scan Clock Digital Trigger (Prior Art)

Figure 43A (Prior Art)


Workshop - Workshop 1
File Edit View Tools Blocks Help
Workshop 1
Undo
Redo
Apply
Blocks
Angular Pos...
Frequency
Resistance
Temperature
Voltage
Voltage
Measurement Setup
Measurements List
Voltage 0
Voltage 1
Voltage 2
Voltage 3
Add New Measurements
Copy Existing Measurements
Remove
Show Details ...
Input Range
Max 10.0000 V
Min -10.0000 V
Sensors & Scaling
<none>
Selection List
Apply these settings to all Measurements
Measurement Timing
Mode
Acquire a Single Sample
Acquire N Samples
Continously Acquire
Sampling Info
1000 Samples
10000.00 Rate (Hz)
Apply current timing to all Groups in task
Task Setup
Advanced Configuration
Event Setup
Data Overview

Figure 43B


Workshop - Workshop 1
File Edit View Tools Blocks Help
Workshop 1
Undo
Redo
Apply
Blocks
Advanced
Configuration Setup
The settings on this page allow you to tweak advanced configuration parameters for your measurements. Hold the mouse pointer over any object to learn more about what it does.
Reset all to Default
Measurement Timing
Scan Clock
PFI_7
Source
10000.00 Rate (Hz)
<Default>
Timebase
Channel Clock
<Default>
Source
1.00 Rate (Hz)
<Default>
Timebase
Measurement Data
Return Data Type
Scaled
Advanced Mathematics
<none>
Stream to Disk
File Path
C:\MyData\Log.dat
Post to the Internet
URL
dstp://localhost/MyWebData
Measurement Triggering
Start
Trigger Type
Digital
Condition
Rising Edge
Source
PFI_0
0.00 Level
0.10 Hysterisis
Stop
Trigger Type
<Default>
None
Condition
Software
Source
SW
0.00 Level
0.10 Hysterisis
Pause
Trigger Type
<Default>
None
Condition
Software
Source
SW
0.00 Level
0.10 Hysterisis
Task Setup
Advanced Configuration
Event Setup
Data Overview

Figure 43C



Acquire N Scans External Scan Clock Digital Trigger

Figure 43D



Triggered Acquisition With E-Series Device

Figure 44A



Triggered Acquisition With High Speed Digitizer

Figure 44B



Triggered Acquisition With High Speed Digitizer With Filtering

Figure 44C



Intermediate Layer (Prior Art)

Figure 45A



Changes For Analog Window Triggering (Prior Art)

Figure 45B



Analog Window Triggering

Figure 45C